


称重传感器 LOAD CELL

SB 称重传感器


SB Load Cell



- Maximum capacity (E_{max}) 额定载荷 (t):
0.5, 1, 2, 3, 5, 7.5
- Be suitable for the fields of Ground scales, Platform Scales, Belt Scales, Industries of Foods, Pharmaceuticals, which has huge important on weighing and control.

适用于地上衡、平台秤、皮带秤、化工、食品、医药等行业配料称重控制

外形尺寸 Dimensions(in mm)



接线图 Wiring code



CAPACITY 载荷 (t)	A	B/G	C	D	E	F	H	J	M	Φ1	Φ2	Φ3
0.5, 1, 2	203	37	43	95	8	30.5	64	98	22	16	32	13
3	203	37	43	95	8	30.5	64	98	22	16	32	15
5, 7.5	235	48	52	110	12	30	66	124	22	22	38	20

技术参数 Specifications

额定载荷 Rated Load	t	0.5, 1, 2, 3, 5, 7.5
额定输出 Rated Output	mV/V	2.0±0.005
零点平衡 Zero Balance	%R.O.	±1
综合误差 Comprehensive Error	%R.O.	±0.02
蠕变 (30 分钟) Creep after 30 minutes	%R.O.	±0.02
推荐激励电压 Recommended excitation voltage	VDC	5-12 /15(max)
输入阻抗 Input impedance	Ω	380±10
输出阻抗 Output impedance	Ω	350±5
绝缘阻抗 Insulation resistance	MΩ	≥5000 (50VDC)
安全过载 Safe overload	%R.C.	150
极限过载 Ultimate overload	%R.C.	300
弹性元件材料 Material		Alloy steel 合金钢
防护等级 Degree of protection		IP67
电缆线长度 The length of the cable	m	0.5t-3t:4m 5t:5m 7.5t:6m
拧紧力矩 Tightening torque	N•m	0.5t-3t: 98N•m 3t: 160N•m 5t: 225N•m 7.5t: 1255N•m